



Cámara tipo Domo

26DIV48

Características:

- IR Dome Camera
- 23pcs ϕ 5mm IR LED
- IR Distance 20m
- Double Glass to Reduce IR Disturbance
- IR Auto-open by CDS Control in Low Lux
- BLC, AWB, AGC
- 3.6mm Board Lens



Especificaciones

MODELO	26DIV48
Model No.	1/3" SONY COLOR CCD,420TV Lines
Number of Pixels	480TV Lines:NTSC:510(H)x492(V); PAL:500(H)x582(V)
Scanning System	NTSC:525 Lines,60 Field/sec, PAL:625 Lines 50 Field/sec
Sync System	Internal Synchronization
Gamma Characteristic	0.45
S/N Ratio	more than 48dB(AGC Off)
Electronic Shutter Time	NTSC 1/60~1/100,000Sec,PAL 1/50~1/100,000Sec;
Minimum Illumination	0 lux with built-in IR LED
IR LED	23 IR LEDs (ϕ 5mm)
IR projecct distance	20 Meters
IR Status	Under 10 Lux by CDS
IR Power On	CDS Auto Control
Lens	3.6/6mm Board Lens
Video Output	1.0Vp-p 75 ohm
Gain Control(AGC)	Auto
Operation Temperature	-10C~ +50C RH95% MAX
Storage Temperature	-20C~ +60C RH95% MAX
Power Supply	DC12V+ ₋ 10%,400mA
Case	White
weight	0.6kg