



**GETESA**  
GENERAL DE TELECOMUNICACIONES, S.L.

## Cámara tipo Domo

### 29DIV42

#### Características:

- Interior
- Sony 1/3" EXview HAD CCD
- Sony DSP (Digital Signal Processor)
- 420TVL
- Automatic White Balance (AWB)
- Vari-focal Auto IRIS
- Lentes: 4-8mm
- Material : Policarbonato, ABS
- DC12V



#### Especificaciones

Modelo	29DIV42
<b>Image Sensor</b>	Sony 1/3" EXview HAD CCD
<b>TV System</b>	NTSC or PAL
<b>Effective Pixels</b>	410K(NTSC)/470K(PAL)
<b>Horizontal Resolution</b>	480TVL
<b>White Balance</b>	Automatic White Balance(AWB)
<b>Scanning System</b>	525 Lines(NTSC), 625 Lines(PAL) 2 : 1 Interlace
<b>Sync. System</b>	Internal(DC12V)
<b>Scanning Frequency</b>	(H)15.734KHz (V)59.94Hz [NTSC], (H)15.625KHz (V)50Hz [PAL]
<b>Min. Illumination</b>	1 Lux
<b>Lens</b>	Vari-Focal Auto IRIS Day&Night Lens(4~9mm: STD, 2.6~6/9~22mm: OPT)
<b>Electrical Shutter</b>	1/60 ~ 100,000(NTSC), 1/50 ~ 100,000(PAL)
<b>S/N Ratio</b>	More than 48dB (AGC Off)
<b>Gamma Correction</b>	0.45 / 1
<b>Video Output</b>	VBS 1.0Vp-p Composite
<b>Function Key</b>	AGC/A.I, E.E/BLC/FLK/Mirror S/W, DC Level Adjustment
<b>Electrical</b>	
<b>Power Source</b>	DC12V
<b>Power Consumption</b>	200mA
<b>Video Output Connector</b>	BNC
<b>Power Output Connector</b>	DC Jack
<b>Environmental</b>	
<b>Operating Temperature</b>	14°F ~ 122°F (-10°C ~ 50°C)
<b>Storage Temperature</b>	22°F ~ 140°F (-30°C ~ 60°C)
<b>Operating Humidity</b>	Up to 90%RH
<b>Mechanical</b>	
<b>Lens Mount</b>	Board Mount Vari-Focal Lens
<b>Material</b>	Polycarbonate, ABS
<b>Color</b>	Black(STD), White(OPT)
<b>Dimensions(mm)</b>	140(W) X 95(H)
<b>Weight</b>	530g