



Cámara IP 43IIV42

Características:

- Formato de compresión H.264
- Soporta grabación local con tarjeta SD, máx. 32Gb
- Resolución de video: 25fps (PAL)/30fps (NTSC)
- Distancia IR: 50-80m (16mm/25mm opcional)
- Entrada/salida de audio: 1 canal
- soporta audio bidireccional
- Soporta EMAIL&FTP
- Alarma de movimiento
- 420TVL.



Especificaciones

43IIV42	420TVL, 0.5LUX,1/3 SONY Super HAD CCD
Auto Iris Control	DC drive
IR LED Distance	80m (25mm lens)(IR On)
Video compression	H.264 Main Profile@Level 3 /MJPEG
Video Definition	CCD PAL:352*288(CIF),704*288(2CIF),704*576(D1); NTSC:352*240(CIF),704*240(2CIF),704*480(D1)
Video Frame Rate	CCD PAL: 1-25frames/second NTSC:1-30frames/second
Video Compression Bitrate	16Kbit/S~8Mbit/S
Supported Protocols	TCP, UDP, IP, HTTP, FTP, SMTP, DHCP, DNS,ARP, ICMP, POP3, NTP, IPsec, UPNP,RTP,RTCP
System Interface	RS232 port (convert to 10M/100M self-adapting Ethernet port, and power supply, Alarm port) Support built-in SD card (Maximum 32GB) Support mobile surveillance
Audio Input	1channel,linear input
Audio Compression	G.726
Audio Output	1channel,RCA interface, linear output
Alarm Input	1 channel on/off input, supporting NO(normally open) or NC(normally close) sense.
Alarm Output	1 channel on/off output,120VAC 1A/24VDC 1A
IP Grade	IP66
Input Power Supply	DC 12V,1A
Operating Temperature	-20~60 °C
Operating Humidity	RH90%MAX
Maximum Power	Less than 8W (IR on)
Dimension	23.3cm(L)*12.4cm(W)*11.8cm(H)
Net weight	2.18kg