

88DIV1200



- ◆ Cámara Domo Analógica Meetática IR
- ◆ Resolución: 1200 TVL, Calidad de Imagen: 1305(H)X977(V)
- ◆ 2D/3D NR, AWB, AGC, Backlight Compensation
- ◆ 2.8-12mm Manual Zoom Lens
- ◆ IR LED: 5X36pcs, IR Distancia: 30M

ESPECIFICACIONES

CAMERA	IMAGE SENSOR	1/3" PIXART CMOS Sensor
	EFFECTIVE PIXEL	1305(H) 977(V)
	HORIZONTAL RESOLUTION	1200 TV Lines
	SCANNING SYSTEM	Progressive Scan
	SYNCHRONIZATION	Internal
	ELECTRONIC SHUTTER	PAL: 1/50s~1/100, 000s; NTSC: 1/60s ~ 1/100, 000s
	MIN. ILLUMINATION	0.01Lux@F1.2(AGC ON), 0Lux IR on
	VIDEO OUTPUT	1 CH CVBS Standard Definition Video Output
	IR RANGE	5X36pcs, IR Range: 30M
LENS	PIXEL	3.0 MP
	IMAGE FORMAT	1/2.7"
	FOCAL LENGTH	2.8-12mm
	APERTURE	F1.4
	MOUNT	M12/Φ14
	FIELD ANGLE(D H V)	1/2.7": 136 108.8 81.6 ~ 39 31.2 23.4
		1/3": 122 97.6 73.2 ~ 36 28.8 21.6
	IRIS	Fixed
	FOCUS	N/A
	ZOOM	N/A
FEATURE	OSD LANGUAGE	N/A
	CAMERA TITLE	N/A
	IMAGE ADJUSTMENT	N/A
	WHITE BALANCE	AUTO
	GAIN CONTROL	AUTO
	DAY&NIGHT	N/A
	BACKLIGHT COMPENSATION	AUTO
	STRONG LIGHT REDUCTION	N/A
	WIDE DYNAMIC RANGE	N/A
	DEFOG	N/A
	SENSE-UP	N/A
	DIGITAL ZOOM	N/A
	NOISE REDUCTION	2D NR
	MOTION DETECTION	N/A
PRIVACY MASK	N/A	
INGRESS PROTECTION	N/A	
GENERAL	POWER SUPPLY	DC12V 10%
	POWER CONSUMPTION	Max5W
	WORKING ENVIRONMENT	-20 C~+60 C / Less than 95%RH (no condensation)
	DIMENSION	131mm x 93mm(H)
	WEIGHT	900g