

Cámara IP

44IIV42

Características:

- Formato de compresión H.264
- Visualización a través de móvil con sistemas Windows/Symbian(S60)
- 1/3" SONY Súper HAD CCD
- Resolución de video: 25fps (PAL)/30fps (NTSC);
- Distancia IR: 50-80m (16mm/25mm opcional)
- Entrada/salida de audio: 1 canal, soporta audio bidireccional
- Soporta EMAIL&FTP
- 10 visores simultaneos pueden acceder a la camara
- Alarma de movimiento
- **420TVL**
- **WIFI.** Support WiFi/802.11b/g wireless network, CDMA1X and GPRS mobile network and surveillance via the mobile phone
- Sistema requerido: Microsoft Windows 98/ME/2000/XP/2003
navegador: Microsoft Internet Explorer 5.x o superior



Especificaciones

P-NVC22WD-42S	420 TVL, 0.5LUX,1/3 SONY Super HAD CCD	
Auto Iris Control	DC drive	
IR LED Distance	80m (25mm lens) (IR On)	
Video compression	H.264 Main Profile@Level 3 , M-JPEG	
Video Definition	CCD	PAL:352*288(CIF),704*288(2CIF),704*576(D1); NTSC:352*240(CIF),704*240(2CIF),704*480(D1)
Video Frame Rate	CCD	PAL: 1-25frames/second. NTSC:1-30frames/second
Video Compression Bitrate	16Kbit/S~8Mbit/S	
Supported Protocols	TCP, UDP, IP, HTTP, FTP, SMTP, DHCP, DNS,ARP, ICMP, POP3, NTP, IPsec, UPNP,RTP,RTCP	
System Interface	10M/100M Ethernet(RJ45), Power, and Audio port; RS485,Alarm,and Reset cable	
	WIFI Port:802.11b/g; Antenna: 5DB / WPA2	
	Support mobile suveillance	
Audio Input	1channel, RCA interface,linear input	
Audio Compression	G.726	
Audio Output	1channel,RCA interface, linear output	
Alarm Input	1 channel on/off input, supporting NO(normally open) or NC(normally close) sense.	
Alarm Output	1 channel on/off output,120VAC 1A/24VDC 1A	
IP Grade	IP66	
Input Power Supply	DC 12V,1A	
Operating Temperature	-20~60 °C	
Operating Humidity	RH90%MAX	
Maximum Power	Less than 8W (IR on)	
Dimension	23.3cm(L)*12.4cm(W)*11.8cm(H)	
Net weight	2.18kg	