

Cámara IP

45IIV48

Características:

- Formato de compresión H.264
- Soporta grabación local con tarjeta SD, máx. 32Gb
- Visualización a través de móvil con sistemas Windows/Symbian (S60)
- 1/4" SONY CCD; Zoom 220X
- Lente: 3.9-85.8mm; 0.5Lux/0.01Lux
- Cámara día y noche
- Resolución de video: 25fps (PAL)/30fps (NTSC)
- Velocidad de giro: Max. Pan: 12°/S Tilt: 12°/S
- Angulo de giro: Horizontal: 360°, Vertical: 0°-90°
- Soporta RS-485, EMAIL&FTP
- Alarma de movimiento; marca de agua
- 480TVL; interior/exterior.



Especificaciones

Modelo	45IIV48
Video compression	Network Spec: H.264 Main Profile@Level 3/MJPEG
VideoCompression Bitrate	16Kbit/S~8Mbit/S
Supported Protocols	TCP, UDP, IP, HTTP, FTP, SMTP, DHCP, DNS,ARP, ICMP, POP3, NTP, IPsec, UPNP,RTP,RTCP
System Interface	10M/100M self-adapting Ethernet port, power supply cable. Support mobile surveillance
preset	Speed Dome Spec: 64presets, can be labeled with editable title
Pan rotation range	360° Endless
Tilt range	Tilt 90°
Manual pan speed	6°/S, 9°/S, 12°/S, 15°/S
Manual vertical speed	6°/S, 9°/S, 12°/S, 15°/S
Communication Protocol	RS485 axis visual control Sony, Hitachi, CNB(Day/night), LG,etc.
IP Grade	IP66
Baud rate (RS485)	2400/4800/9600/19200bps
Operating Temp	Environmental 5°C(healter)-+50°C(Fan)
Operating Humidity	RH90%MAX
Power Supply	Electrical Spec: DC14V(2A)---15V(2A)
Dome Motor	DC14V—15V(0.5A)
Camera lens motor	DC12V/100mA
Camera power supply	12V/1A

Mas especificaciones

Image Sensor	1/4" SONY CCD. 1/4" Sony Exview CCD (Day/Night Mode)
Zoom Camera	Z2
Resolution	480TVL
Min. Illumination	0.5Lux/0.01Lux
Zoom Magnification	220X
Zoom Length	3.9-85.8mm
Angle of View	Wide47°Tele3°
privacy masking	NO