

Cámara Camuflada


500NF42

Características:

- Cámara oculta
- 420TVL
- Lente: 3.6mm
- 0.2 Lux
- Ángulo de visión ajustable
- 1 / 3 "CCD color
- Lente Mega píxeles



Dimensiones



Especificaciones

Modelo		500NF42
Scanning System	NTSC	525 lines 2:1 interlace
	PAL	625 lines 2:1 interlace
Scanning Frequency	NTSC	15,734Hz(H) , 60Hz(V)
	PAL	15,625Hz(H) , 50Hz(V)
Effective Pixels	NTSC	510(H) x 492(V)
	PAL	500(H) x 582(V)
Electronic Shutter	NTSC	1/60-100,000sec.
	PAL	1/50-100,000sec
Image Device		1/3" SONY Super HAD CCD
Horizontal Resolution		420 TV lines
Sensitivity		0.2Lux
Signal to Noise		More than 48dB
Gain Control		Auto
White Balance		Auto ATW 2500-9500 ° K
BLC		Auto
Gamma Correction		0.45
SYNC System		Internal
Lens		Mega pixel Lens 4.0mm
Video Output		1.0 Vp-p, 75 Ohm
Power Requirement (± 10%)		DC12V, 500mA
Power Consumption (± 10%)		80mA
Operation Temp.		Operating: -10 ~ + 55 °C , Storage: -30 ~ + 70 °C , Humidity:0~95%RH
Dimensions (mm)		Main body:280(H) x 230(W), Bracket:195(H) x 100(W) x 71(D)
Weight (N.W)		1135g