

81TIV70



Imaging Sensor	1 / 3" SONY 960H HAD CCD
Total Pixel	PAL: 1020(H)×596(V);NTSC: 1020(H)×508(V)
Effective Pixel	PAL: 1020(H)×596(V);NTSC: 976(H)×494(V)
Signal System	PAL/ NTSC
Syn. System	Internal Synchronization
Shutter speed	PAL:1/50~1/100000s; NTSC:1/60~1/100000s
S/N Ratio	More than 120dB (WDR ON)
Video Output	1.0Vp-p, 75 ohms,
Horizontal resolution	700TVL
SENSE UP	OFF/x2/x4/x8/x16/x32/x64/x128/x256
Mini. Illumination	0 Lux with IR ON
White Balance	ATW/AWB/MANUAL
D/N Switch	AUTO/DAY/NIGHT
AGC	OFF/LOW/MIDDLE/HIGH
FREEZE	ON/OFF
D.ZOOM	ON/OFF
3D-DNR	0-5
D-WDR	YES
TITLE	YES
OSD language	English/Chinese
BRIGHTNESS	0-90 adjustable
Gamma Correction	0.05-1 adjustable
Motion Detection Zone	ON/OFF (4 Zones), can auto zoom
ALARM	YES
Privacy Zone	ON/OFF (8 Zones)
Mirror	OFF/HORI/VERT/ROTATE
IR Range	72 PCS 5MM IR LEDs, 70 Meter IR distance
Lens	5-15mm Motorized Zoom Lens Series
Weather Proof Standar	IP-66
Power supply	DC12V
Power consumption	600mA
Operation temperature	-10~+60 Celsius
Storage temperature	-20~+70 Celsius
Dimensions	185*98*91mm