

---

## IP-76DIV

**1.0 Mega Pixel P2P Cámara Domo Antivandálica IP con IR: 30m**

**Lente Vari-focal**



- 1) Incluye lente 2.8-12mm, con IR-Cut
- 2) 36pcs  $\Phi$ 5mm LED, IR distancia: 30m
- 3) Cámara Ip Domo Antivandálica
- 4) 1.0MP/720P tiempo real, Main Stream: 1280\*720@30FPS, Sub Stream: 704\*576@9FPS

---

### **Características Generales:**

- 1) Dual stream encoding (H.264/MJPEG)
- 2) Soporta navegadores Firefox, Safari y Chrome
- 3) Soporta vista desde Android, Iphone, Windows, Blackberry, Symbian
- 4) Soporta software multipantalla y CMS (64CH a la vez)
- 5) Soporta software en la nube
- 6) Soporta RTSP/Email/ARSP/FTP/PPPOE/DHCP/DDNS/NTP/UPnP/DAS/IP
- 7) Soporta grabación por detección de movimiento con DVR y P2P NVR apropiado
- 8) Soporta ultimo protocolo Onvif

## Especificaciones

<b>Model</b>	<b>IP-76DIV</b>
<b>Camera</b>	
Image Sensor	1.0 Mega pixels, 1/4" CMOS Sensor, Hi3518E
Effective Pixels	1.0MP: 1280*720
Scanning System	Progressive
Electronic Shutter Speed	1/25~1/100,000 sec
Min. Illumination	0.6Lux/F1.2(color),0.08Lux/F1.2(B/W) (0 Lux when IR ON)
S/N Ratio	>50dB
<b>Lens</b>	
Focal Length	HD 2.0 Mega pixel 2.8-12mm lens, with IR-Cut
Max Aperture	F1.2
Focus Control	Manual
Angle of View	90°(Horizontal)
Lens Type	M12
<b>Camera Features</b>	
IR Distance	36pcs $\Phi$ 5mm LED, IR distance: 30m
Wide Dynamic Range (WDR)	No
Day/Night	Auto(ICR)/Color/B/W
Backlight Compensation (BLC)	Auto
White Balance	Auto
Gain Control	Auto
Noise Reduction	Yes
Motion Detection	Yes
Privacy Masking	Yes

<b>Video</b>	
Compression	H.264 / AVI format
Main Stream	720P: 1280*720@30FPS, 1~30FPS adjustable
Sub Stream	D1: 704*576@9FPS
Bit Rate	CBR and VBR, 0,1M~6Mbps
<b>Network</b>	
Ethernet	RJ-45 (10/100Base-T)
Protocol	RTSP/Email/ARSP/FTP/PPPOE/DHCP/DDNS/NTP/UPnP/DAS/IP authority
ONVIF	ONVIF Ver. 2.2
Max. User Access	5 users
Smart Phone	iPhone, Android, Windows Mobile, BlackBerry, Symbian
<b>Audio</b>	
Audio Input	N/A
Audio output	N/A
Audio Process	N/A
<b>Auxiliary Interface</b>	
Memory Slot	N/A
Alarm Input	N/A
Alarm Output	N/A
Alarm Function	Motion detection
	Center warning and picture pop-up linkage supported ( after motion detection)
<b>General</b>	
Operation function	Support WEB configuration; OSD; Real-Time Video transmission; Motion detection, Snap, CMS, VMEYE
Power Supply	DC12V
Power Consumption	<5W
Working Environment	-10°C~+60°C, 10%~90%
Dimensions	
Weight	